

Farrington Small Eco (Black)



Code	FARRINGTON-S-BLACK-EU-G2
Output	4.9kW
Log length	360mm
Width	495mm
Height	638mm
Depth	356mm
Nett efficiency	77.8%
Ecodesign Ready	Yes

Features

- Lifetime guarantee
- Exceeds Ecodesign standards when burning wood or solid fuel
- Approved for use in Smoke Control Areas
- Stainless steel ash pan and throat plate
- 5" spigot as standard / 6" available free of charge on request
- Direct air compatible
- Preheated airwash system for clean glass
- Externally controlled riddling grate from either side
- Range of removable door handle designs
- Stocked in Matt Black or Grey
- Rear heat shield to allow closer positioning to combustibles
- Height adjusting legs as standard
- Choice of standard detachable handle or optional detachable wooden handle

Farringdon Small Eco (Black) - Technical Information

Code	FARRINGDON-S- BLACK-EU-G2
Output range	1.5-7kW
Nett efficiency	77.8 %
Width	495mm
Height	638mm
Depth	356mm
Height to centre of rear flue	520mm
Added height when on stand	768mm
Added height when on log store	948mm
Depth of back to centre of top flue	112mm
Flue diameter	127mm
Suitable for 12mm hearth	Yes
Under hearth temperature	43°C
Suitable for direct air supply kit	Yes
Packed weight	106kg
Maximum log length	360mm

Emissions levels - Wood Fuel

CO @ 13% O2	0.11 %
Din+ Particulate Matter	13.0 Nmg/m3
NOx	79.0 Nmg/m3
Organic Gaseous Compounds	92.0 Nmg/m3

Emissions levels - Solid Fuel

CO @ 13% O2	0.06 %
Din+ Particulate Matter	5.0 Nmg/m3
NOx	79.0 Nmg/m3
Organic Gaseous Compounds	5.0 Nmg/m3

Minimum Distance To Combustibles

To rear of stove	350 mm
To sides of stove	500 mm

