



Product Fiche

Supplier name	Arada
Product Code	LAGOM
Energy Efficiency Class (wood)	A+
Direct Heat Output (wood)	4 Kw
Indirect Heat Output (wood)	N/A
Energy Efficiency Index (wood)	107.8
The useful energy efficiency at nominal heat output and at minimum load (wood)	80.5 %

Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:

Product should be installed in accordance with local building regulations.
Appliance will become very hot during use.

Dimensions

Width	528 mm
Height	974 mm
Depth	398 mm
Flue Diameter	149 mm
Depth from back to centre of top flue	199 mm
Axis height of rear flue	863 mm
Ideal log length / diameter	250mm

Performance

	Wood Fuel
Energy Efficiency Class	A+
Nett Efficiency	80.5 %
Nominal Output	4.0 kW
Mean CO Emission (@13% O ₂)	1192 mg/m ³
Mean CO₂ Emission	9.59
DIN+ particulate	15 Nmg/m ³
Mean NO_x Emission (@13% O ₂)	111 Nmg/m ³
Mean OGC Emission (@13% O ₂)	68 Nmg/m ³
Flue Gas Mass Flow	4 g/s
Flue Gas Temperature	247 °C
Average wood consumption	1.2 kg/hour

Features

Stove body type	Freestanding
Ecodesign Ready	Yes
Approved for smoke control areas	No
Suitable for direct air connection	Yes
Suitable for non-combustible 12mm hearth	Yes
Weight nett (unpacked kg)	123 Kg

Minimum distance to combustibles

Single Walled Flue, *without* Rear Heat Shield fitted

Rear	100 mm
Side	100 mm
Top	1200 mm

Direct air spigot location

When viewing the rear side of stove

Spigot diameter	125 mm
Spigot orientation	Vertical
Height from floor	311 mm
Axis distance from rear	82 mm
Lateral position	Centre

This stove is produced under licence by our EU partner.